

Single-Lamp System

- Configured for Maxim and Maxim Cool Cure cassettes
- Cabinet houses single lamp power supply
- Expandable
- Can handle any single station application

The SLS is designed for maximum printing speeds and competitively priced to deliver a greater return on your investment. With its plug-and-play expansion capabilities, the SLS allows the narrow and medium web printer to start with a single lamp and grow as business permits.

With every installation, you receive in-depth technical support from our staff of experienced UV printing specialists on a 24-7 basis. Also UVTechnology can support all your UV curing system needs with our full line of aftermarket replacement bulbs and accessories for your convenience.



EXPANSION

Plug-and-play connection provides an easy and affordable way to add lamps with a single press interface and multiple operator messaging terminals.

SAFETY

The SLS system meets current NEC, NFPA and CE standards using finger safe components and fault protection devices.

USER FRIENDLY

SLS comes with an intuitive menu-driven interface for system operation and programming.

INCREASED PRODUCTIVITY

An auto cool down feature allows for faster restarts to increase print shop productivity.

HEAT MANAGEMENT

The use of a variable frequency drive for blower control enables better management of lamp temperature for overall lower web temperatures and reduced noise.

FLEXIBILITY

The optional speed wheel interface allows the SLS to be used with virtually any press and makes integration to the press quick and simple.

CASSETTE SYSTEMS

Compatible with:

- Maxim
- Maxim Cool Cure

SLS

UV POWER SUPPLY SYSTEM

Multiple Power Levels

- 33%, 66% and 100%

Available Systems

- 50 Hz 230/380/415
- 60 Hz 208/240/480

Control Features

- Amp meter
- Three power levels
- Constant wattage ballast
- Remote interface messaging terminal
- Variable frequency drive blower regulates lamp temperature
- Finger safe components
- CE compliant

Cabinet Dimensions

- Height
36 in./914 mm
- Width
30 in./762 mm
- Depth
24 in./610 mm
- Riser
6 in./152 mm

Optional

- Speed wheel interface



MARKANDY

Mark Andy Inc.
Tel +1 636 532 4433
Fax +1 636 532 1510
18081 Chesterfield Airport Rd.
P.O. Box 1023
Chesterfield, MO USA
63006-1023

www.markandy.com